

# PAT100 SERIES

## Handheld portable appliance testers



- **Simple Tick/Cross, pass/fail indication plus measurement**
- **Battery powered with rechargeable options**
- **Includes 250 V Insulation and Leakage testing for safe IT testing and surge protected devices**
- **Testing portable and fixed electrical equipment**
- **10 mA and 30 mA Portable RCD lead testing (PAT150)**
- **Adjustable PASS test limits (PAT150)**
- **Substitute and Mains powered leakage testing (PAT150)**
- **Tough, rubber armoured with built-in front cover, hardened, scratch proof display window**

### DESCRIPTION

The PAT100 series of hand help portable appliance testers enable simple, fast safety testing in all environments including offices, shops and business units. It is ideally suited to training organisations with a very short learning curve and tough, reliable functionality.

With rubber armoured cases and fitted with hardened, scratch proof glass, the PAT100s are exceptionally tough instruments.

Battery powered operation makes the PAT100s perfect for those locations where an electrical supply is not available, inconvenient or unsafe, especially building sites and warehouses. The PAT100 series conforms to all UK and European requirements for electrical safety testing.

### Test groups

Test groups enable the correct sequence of tests to be performed automatically with minimum intervention by the user. This keeps testing simple, reduces test times to a minimum and helps to prevent testing errors.

#### PAT120:

- The PAT120 model has test groups available for Class I, Class II and Extension/Power leads.
- Fixed PASS limits.
- Insulation testing at 500 V (default) or 250 V can be selected at the start of the test.
- Leakage testing uses a "Substitute Leakage" also known as the "Alternative" method to remove the need for a mains supply during test.

#### The PAT150:

- The PAT150 has additional tests available for testing portable RCDs (PRCDs) of 10 mA and 30 mA.
- Separate tests for Continuity, Insulation, mains powered leakage testing and SELV measurements can be made using the Quick Test (QT) button.
- Test group pass limits and test duration can be configured by the user.
- Bond lead resistance can be nulled to reduce measurement errors.
- Live circuit measurement is available for testing the mains supply and socket polarity or electrical circuit voltage to 300 V ac.
- Can be used for testing fixed appliances.

#### Continuity test

Used for measuring the proper bonding of all metal parts of a class I device to the protective conductor.

Tests are performed at 200 mA dc in both polarities to be compliant with international and UK regulation or recommendations. This test is safe to perform on equipment where higher test currents could cause damage.

#### Insulation testing

Used for measuring the separation of conductive parts or conductors from earth. This test is usually performed at 500 V dc. The PAT100 series maintain the necessary test voltage down to 0.5 Mohms.

## SPECIFICATIONS

### ENVIRONMENTAL CONDITION:

<b>Operating ambient</b>	20°C
<b>Humidity</b>	Nominal humidity

### CONTINUITY TEST

<b>Test voltage</b>	Compliance Voltage: +4V dc -0 % /+10 % (open circuit)
<b>Test current</b>	Bi-directional +200mA -0% + 50mA (into 2Ω load)
<b>Continuity accuracy</b>	Resistance: ± 5% ± 3 digits (0 to 19.99 Ω)
<b>Resistance resolution</b>	10 mΩ
<b>Display range</b>	0.01 to 19.99Ω
<b>Continuity test nulling</b>	up to 9.99 Ω
<b>Test time</b>	User selectable from 2 sec to 20 sec or selected during test to 180sec

### INSULATION TEST

<b>Insulation test</b>	250V dc -0 % /+25 % open circuit 500V dc -0 % /+25 % open circuit ≥ 500V 0% dc across 0.5 MΩ load
<b>Short circuit/charge current</b>	< 2mA dc
<b>Insulation accuracy</b>	±3% ±10 digits (0 to 19.99 MΩ)
<b>Resolution</b>	0.01 MΩ
<b>Display range</b>	0.10 MΩ to 99.99 MΩ
<b>Test duration</b>	User selectable from 2 sec to 20 sec or selected during test to 180sec

### SUBSTITUTE LEAKAGE TEST

<b>Leakage current</b>	Accuracy ± 5% ± 3 digits
<b>Test frequency</b>	Nominal mains frequency 50Hz
<b>Test voltage</b>	< 50V ac
<b>Resolution</b>	0.01mA
<b>Display range</b>	0.10 to 19.99mA
<b>Test duration</b>	User selectable from 2 sec to 5 seconds

### Reading corrected to 230V ac.

### DIFFERENTIAL LEAKAGE CURRENT

<b>Test voltage</b>	Nominal supply voltage 230 V ac
<b>Test frequency</b>	Nominal mains frequency 50 Hz
<b>Test accuracy</b>	±5% ±3d ±3uA/A
<b>Resolution</b>	0.01 mA
<b>Display range</b>	0.10 to 19.99 mA
<b>Test duration</b>	User selectable from 2 sec to 5 seconds

### TOUCH CURRENT TEST

<b>Test voltage</b>	Nominal mains 230 V ac
<b>Test frequency</b>	Nominal mains 50 Hz
<b>Test accuracy</b>	± 5% ± 3 digits
<b>Resolution</b>	0.01 mA
<b>Display range</b>	0.10 to 3.99 mA
<b>Test duration</b>	User selectable from 2 sec to 5 sec

### SELV DEVICE TEST

<b>Test voltage</b>	0 to 300 V ac
<b>Measurement accuracy</b>	± 3% ± 3 digits
<b>Resolution</b>	0.1 V ac
<b>Display range</b>	0.1 to 300 V ac

### EXTENSION LEAD TEST

#### Test includes Insulation and Bond tests.

<b>Test voltage</b>	5V
<b>Polarity</b>	Lead OK Live/neutral shorted Live/neutral reversed Live/neutral open circuit

### PORTABLE RCD TEST

<b>Test voltage</b>	Nominal mains 230 V
<b>Test frequency</b>	50Hz
<b>Test current accuracy</b>	+2% to +8% (1 x I, 5 x I)
<b>Trip time accuracy</b>	±1% ± 1ms
<b>Trip time resolution</b>	0.01ms
<b>Display range</b>	0 to 200ms (1 x I) 0 to 40ms (5 x I)

### MAINS SUPPLY TEST

<b>Frequency measurement range</b>	50 Hz
<b>Test voltage</b>	40 to 300V ac
<b>Accuracy</b>	± 3% ± 3 digits
<b>Resolution</b>	0.1Vac
<b>Display range</b>	40 to 300V ac

### CIRCUIT TEST

#### (Carried out automatically, not available to user)

<b>Test voltage</b>	5V
<b>Test frequency</b>	Nominal Mains 50 Hz
<b>Test current</b>	< 100mA short circuit

### Safety

**Instrument designed to IEC 61010-1: 2012**  
**Test leads designed to IEC 61010-031: 2005**  
**300 volts to Earth Category II**  
**Mains fuse protection to 250 volts rms ac**

## EMC

**Design to meet IEC 61326-1: 2006 and IEC 61326-2-2: 2005.**

## Fuse

(user replaceable)

UK variants has mains plug fuse

One F 100 mA 250 V 5 x 20 mm HBC fuse.

## ENVIRONMENTAL

**Operating temperature range** 0°C to +40°C

**Storage temperature range** -20°C to +60°C

**Humidity** 90%RH @ +10°C +30°C  
75%RH @ +30°C to +40°C

**Maximum altitude** 2,000m to full safety spec.

**IP rating** IP40 (with front cover closed)

## MECHANICAL

### BATTERIES

**Battery life** 3 days based on 120 tests/  
day using 2000 mAh Alkaline  
batteries

**Battery type** Supply voltage  
12 Vdc (Alkaline AA LR6)  
9.6 Vdc (NiMH AA LR6)

## WEIGHT

PAT120 (instrument only): 1150 g (40.4 oz)

Shipping weight: 2370g (83.6 oz)

PAT150 (instrument only): 1300 g (45.8 oz)

Shipping weight: 2795g (98.6 oz)

PAT150R (instrument only): 1300 g (45.8 oz)

Shipping weight: 2975g (104.9 oz)

## DIMENSIONS

**Dimensions (instrument and case)** 203mm (L) x 148mm (W) x 78mm (H)  
(8 x 5.7 x 3.2 inches)

**Dimensions (instrument and packaging)** 456mm(L) x 178mm (W) x 89mm (H)  
(18 x 7.1 x 3.5 inches)

Product selection table:	UK		Germany		Dutch Spain Belgium		Belgium Poland		Switzerland		Australia New-Zealand	
	PAT120-UK	PAT150-UK	PAT120-DE	PAT150-DE	PAT120-EU	PAT150-EU	PAT120-FR	PAT150-FR	PAT120-CH	PAT150-CH	PAT150-AU	
<b>Connector Interfaces</b>												
Mains Test Socket	BS1363		CEE 7/4 Schuko				CEE 7/5 French		Swiss SEV 1011		AS/NZS 3112 (15A)	
<b>Power Supply</b>												
AA alkaline/NiMH	■	■	■	■	■	■	■	■	■	■	■	
Rechargeable (PAT150R)*		■		■		■		■		■	■	
<b>Testing</b>												
Protective Earth Resistance	■	■	■	■	■	■	■	■	■	■	■	
250 V insulation	■	■	■	■	■	■	■	■	■	■	■	
500 V insulation		■		■		■		■		■	■	
Cable test	■	■	■	■	■	■	■	■	■	■	■	
Live protective conductor current		■		■		■		■		■	■	
Live touch current		■		■		■		■		■	■	
Substitute leakage	■	■	■	■	■	■	■	■	■	■	■	
Functional test (part of Live leakage test)		■		■		■		■		■	■	
10 mA PRCD		■		■		■		■		■	■	
30 mA PRCD		■		■		■		■		■	■	
SELV voltage		■		■		■		■		■	■	
Lead resistance nulling		■		■		■		■		■	■	
<b>Function Keys</b>												
Class 1	■	■	■	■	■	■	■	■	■	■	■	
Class 2	■	■	■	■	■	■	■	■	■	■	■	
Lead/cord	■	■	■	■	■	■	■	■	■	■	■	
PRCD		■		■		■		■		■	■	
Single test		■		■		■		■		■	■	
LCD Backlight	■	■	■	■	■	■	■	■	■	■	■	
Setup		■		■		■		■		■	■	
On/Off	■	■	■	■	■	■	■	■	■	■	■	
<b>Standard Accessories</b>												
4mm plug lead probe + croc clip	1	2	1	2	1	2	1	2	1	2	2	
Extension lead adaptor	BS1363		IEC 83:1975 Std C 1b				SN SEV 1011		AS/NZS 3112:2000			
AC Charger Adaptor		■		■		■		■		■	■	
Mains Supply Cord		■		■		■		■		■	■	
Carry case	■	■	■	■	■	■	■	■	■	■	■	

**Note: The rechargeable version of the PAT150 has the identifier (R).**

## ORDERING INFORMATION

Description	Order Code	Description	Order Code
PAT120-CH PORTABLE APPLIANCE TESTER	1003-074		
PAT120-DE PORTABLE APPLIANCE TESTER	1003-066		
PAT120-DE-RS PORTABLE APPLIANCE TESTER	1003-067		
PAT120-EU PORTABLE APPLIANCE TESTER	1003-070		
PAT120-FR PORTABLE APPLIANCE TESTER	1003-072		
PAT120-UK PORTABLE APPLIANCE TESTER	1003-062		
PAT120-UK-RS PORTABLE APPLIANCE TESTER	1003-063		
PAT150-AU PORTABLE APPLIANCE TESTER	1003-077		
PAT150-CH PORTABLE APPLIANCE TESTER	1003-075		
PAT150-DE PORTABLE APPLIANCE TESTER	1003-068		
PAT150-DE-RS PORTABLE APPLIANCE TESTER	1003-069		
PAT150-EU PORTABLE APPLIANCE TESTER	1003-071		
PAT150-FR PORTABLE APPLIANCE TESTER	1003-073		
PAT150-UK PORTABLE APPLIANCE TESTER	1003-064		
PAT150-UK-RS PORTABLE APPLIANCE TESTER	1003-065		
PAT150R-AU PORTABLE APPLIANCE TESTER	1003-435		
PAT150R-CH PORTABLE APPLIANCE TESTER	1003-434		
PAT150R-DE PORTABLE APPLIANCE TESTER	1003-430		
PAT150R-DE-RS PORTABLE APPLIANCE TESTER	1003-431		
PAT150R-EU PORTABLE APPLIANCE TESTER	1003-432		
PAT150R-FR PORTABLE APPLIANCE TESTER	1003-433		
PAT150R-UK PORTABLE APPLIANCE TESTER	1003-428		
PAT150R-UK-RS PORTABLE APPLIANCE TESTER	1003-429		
		<b>Included accessories for PAT120</b>	
		Extension lead adaptor BS1363	1001-234
		Continuity/earth bond lead	1001-233
		Carry case	1005-075
		<b>PAT100 range ~ Included accessories for PAT150</b>	
		Continuity/earth bond lead	1001-233
		SELV/mains voltage test lead Red x1	1005-077
		Extension lead adaptor BS1363	1001-234
		Extension lead adaptor Schuko	1001-235
		Extension lead adaptor Australia	1001-236
		Extension lead adaptor Switzerland	1005-081
		Mains plug test lead	6231-601
		Mains plug test lead (CEE 7/7)	1005-078
		Mains plug test lead (AS/NZS 3112)	1005-080
		Carry case	1005-075
		<b>Included accessories for PAT150R</b>	
		AC Mains charger – multi-country	1003-436
		<b>Optional accessories</b>	
		Plug adaptor IEC C6 - C13	1001-232
		110 V Extension lead adaptor	6220-639
		415 V adaptor lead (4-pin) to BS1363 (16 A)	1000-767
		415 V adaptor lead (5 pin) to BS1363 (16 A)	1000-770

**UK**  
 Archcliffe Road Dover  
 CT17 9EN England  
 T +44 (0) 1304 502101  
 F +44 (0) 1304 207342  
 UKsales@megger.com

**UNITED STATES**  
 4271 Bronze Way  
 Dallas TX 75237-1019 USA  
 T 800 723 2861 (USA only)  
 T +1 214 333 3201  
 F +1 214 331 7399  
 USsales@megger.com

**OTHER TECHNICAL SALES OFFICES**  
 Valley Forge USA, College Station USA,  
 Sydney AUSTRALIA, Danderyd SWEDEN,  
 Ontario CANADA, Trappes FRANCE,  
 Oberursel GERMANY, Aargau SWITZERLAND,  
 Kingdom of BAHRAIN, Mumbai INDIA,  
 Johannesburg SOUTH AFRICA, Chonburi THAILAND

**CERTIFICATION ISO**  
 Registered to ISO 9001:2004 Cert. no. Q 09290  
 Registered to ISO 14001:2000 Cert. no. EMS 61597  
**PAT100\_DS\_en\_V01**  
[www.megger.com](http://www.megger.com)  
 Megger is a registered trademark